
1.5W,9.1 - 100V Zener Diodes

Features

- Low leakage current
- Available in unidirectional
- Glass passivated junction
- Zener voltage tolerance is ±5%
- Total power dissipation: Max 1.5W
- Moisture sensitivity: level 1, per J-STD-020
- Halogen-free according to IEC 61249-2-21 definition
- AEC-Q101 qualified

Pb
RoHS
COMPLIANT



SMB (DO-214AA)

Applications

Protection from high voltage, high energy transients, voltage stabilization and automotive applications.

Absolute Maximum Ratings (T_A=25°C unless otherwise noted)			
Parameter	**Symbol**	**Ratings**	**Unit**
Zener voltage	V_Z	See Next Table	V
Power dissipation at T_L=75℃	P_{tot}	1.5	W
Maximum instantaneous forward voltage at 200mA	V_F	1.2	V
Operating junction and storage temperature range	T_J, T_{STG}	-55 to +150	℃

Thermal-Mechanical Specifications (T_A=25℃ unless otherwise noted)			
Parameter	**Symbol**	**Typ**	**Unit**
Thermal Resistance, Junction to Ambient	R_{thJA}	85	°C /W
Thermal Resistance, Junction to Case	R_{thJC}	15	°C /W
Thermal Resistance, Junction to Lead	R_{thJL}	20	°C /W

Note：

1.The thermal resistance from junction to ambient, case or lead, mounted on P.C.B with 5×5mm copper pads

Electrical Characteristics (TA = 25 °C unless otherwise noted)

Part Number	Marking	V_Z at I_{ZT} (V)			I_{ZT} (mA)	Maximum zener impedance		I_{ZK} (mA)	Maximum reverse leakage at V_R (μA)	Test voltage V_R (V)	Maximum Zener Current
		Min	Typ	Max		Z_{ZT} at I_{ZT} (Ω)	Z_{ZK} at I_{ZK} (Ω)				IZM (mA)
A1.5SMBZ9.1A	A9V1A	8.65	9.1	9.56	41.2	4	500	0.5	5	7.0	165
A1.5SMBZ10A	A10A	9.50	10	10.50	37.5	4.5	500	0.25	5	8.0	150
A1.5SMBZ11A	A11A	10.45	11	11.55	34.1	5.5	550	0.25	1	8.4	136
A1.5SMBZ12A	A12A	11.40	12	12.60	31.2	6.5	550	0.25	1	9.1	125
A1.5SMBZ13A	A13A	12.35	13	13.65	28.8	7	550	0.25	1	9.9	115
A1.5SMBZ15A	A15A	14.25	15	15.75	25.0	9	600	0.25	1	11.4	100
A1.5SMBZ16A	A16A	15.20	16	16.80	23.4	10	600	0.25	1	12.2	94
A1.5SMBZ18A	A18A	17.10	18	18.90	20.8	12	650	0.25	1	13.7	83
A1.5SMBZ20A	A20A	19.00	20	21.00	18.7	14	650	0.25	1	15.2	75
A1.5SMBZ22A	A22A	20.90	22	23.10	17.0	17.5	650	0.25	1	16.7	68
A1.5SMBZ24A	A24A	22.80	24	25.20	15.6	19	700	0.25	1	18.2	63
A1.5SMBZ27A	A27A	25.65	27	28.35	13.9	23	700	0.25	1	20.6	56
A1.5SMBZ30A	A30A	28.50	30	31.50	12.5	26	750	0.25	1	22.8	50
A1.5SMBZ33A	A33A	31.35	33	34.65	11.4	33	800	0.25	1	25.1	45
A1.5SMBZ36A	A36A	34.20	36	37.80	10.4	38	850	0.25	1	27.4	42
A1.5SMBZ39A	A39A	37.05	39	40.95	9.6	45	900	0.25	1	29.7	38
A1.5SMBZ43A	A43A	40.85	43	45.15	8.7	53	950	0.25	1	32.7	35
A1.5SMBZ47A	A47A	44.65	47	49.35	8.0	67	1000	0.25	1	35.8	32
A1.5SMBZ51A	A51A	48.45	51	53.55	7.3	70	1100	0.25	1	38.8	29
A1.5SMBZ56A	A56A	53.20	56	58.80	6.7	86	1300	0.25	1	42.6	27
A1.5SMBZ62A	A62A	58.90	62	65.10	6.0	100	1500	0.25	1	47.1	24
A1.5SMBZ68A	A68A	64.60	68	71.40	5.5	120	1700	0.25	1	51.7	22
A1.5SMBZ75A	A75A	71.25	75	78.75	5.0	140	2000	0.25	1	56.0	20
A1.5SMBZ82A	A82A	77.90	82	86.10	4.6	160	2500	0.25	1	62.2	28
A1.5SMBZ91A	A91A	86.45	91	95.55	4.1	200	3000	0.25	1	69.2	16
A1.5SMBZ100A	A100A	95.0	100	105.0	3.7	250	3100	0.25	1	76.0	15

Ratings and Characteristics Curves (TA = 25℃ unless otherwise note)




Fig.1 – Power Derating Curve




Fig.2 – Typical Zener Voltage





Fig.3 – Typical Zener Voltage

Package Outline Dimensions

in inches (millimeters)

SMB (DO-214AA)



Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd.or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.
(http://www.goodark.com)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.