


N-Channel 150V (D-S) Power MOSFET

Features


- 100% Avalanche Tested
- Extremely Low Losses with Low FOM $R_{DS(on)} \cdot Q_g$
- Halogen Free, Pb-Free
- RoHS Compliant



TOLL

Applications

- DC/DC
- Synchronous Rectification in SMPS
- Hard Switching and High Speed Circuit



Absolute Maximum Ratings ($T_J=25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain Source Voltage	V_{DS}	150	V
Gate Source Voltage	V_{GS}	± 20	V
Drain Current, Continuous $V_{GS}=10\text{V}$	I_D	$T_C=25^\circ\text{C}$	A
		$T_C=100^\circ\text{C}$	
Drain Current, Pulsed (Note 1)	I_{DM}	1209	A
Single Avalanche Energy (Note 2)	E_{AS}	1742	mJ
Power Dissipation	P_D	$T_C=25^\circ\text{C}$	W
		$T_C=100^\circ\text{C}$	
Operating Junction/ Storage Temperature Range	T_J/ T_{STG}	-55 to +175	$^\circ\text{C}$

Note 1: Single Pulse; $t_p \leq 1\text{us}$.

Note 2: $V_{DD} = 75\text{V}$, $V_{GS} = 10\text{V}$, $L = 1\text{mH}$, starting $T_J = 25^\circ\text{C}$.

Thermal Characteristics

Parameter	Symbol	Max	Unit
Thermal Resistance Junction to Case	R_{thJC}	0.29	$^\circ\text{C/W}$
Thermal Resistance Junction to Ambient (Note 3)	R_{thJA}	25	$^\circ\text{C/W}$

Note 3: Device mounted on 1 square inch FR4 PCB board, with 2oz single-sided copper, in a 25°C still air environment.

Electrical Characteristics (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	150	--	--	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =150V, V _{GS} =0V	--	--	1	uA
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _{DS} =250uA	2.5	3.4	4.5	V
Gate Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	--	--	±100	nA
Drain-Source On-state Resistance (Note 4)	R _{DS(on)}	V _{GS} =10V, I _D =80A	--	2.2	2.6	mΩ
Total Gate Charge	Q _g	V _{GS(off)} =0V, V _{GS(on)} =10V, V _{DD} =75V, I _D =20A	--	110	--	nC
Gate Source Charge	Q _{gs}		--	33	--	
Gate Drain Charge	Q _{gd}		--	22	--	
Turn-on Delay Time	t _{d(on)}	V _{GS} =10V, V _{DD} =75V, I _D =20A, R _G =3Ω	--	22	--	ns
Turn-on Rise Time	t _r		--	21	--	
Turn-off Delay Time	t _{d(off)}		--	63	--	
Turn-off Fall Time	t _f		--	28	--	
Gate Resistance	R _g	V _{GS} =0V, f=1MHz, open drain	--	1.1	--	Ω
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =75V, f=500KHz	--	8178	--	pF
Output Capacitance	C _{oss}		--	1978	--	
Reverse Transfer Capacitance	C _{rss}		--	25	--	

Reverse Diode Characteristics (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Current, Continuous	I _{SD}	T _C =25°C	--	--	302	A
Diode Forward Voltage (Note 4)	V _{SD}	I _F =2A, V _{GS} =0V	--	--	1.2	V
Reverse Recovery Time	T _{rr}	I _F = 20A, di/dt = 100 A/μs	--	91	--	ns
Reverse Recovery Charge	Q _{rr}		--	549	--	nC

Note 4: Pulse test; pulse width ≤ 380μs, duty cycle ≤ 1%.

Typical Characteristics Curves ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 1: Output Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Gate-Source Voltage




Figure 4: On-Resistance vs. Drain Current and Gate Voltage




Figure 5: On-Resistance vs. Junction Temperature




Figure 6: Source-Drain Diode Forward Voltage

Typical Characteristics Curves ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 7: Gate Threshold Variation vs. Junction Temperature




Figure 8: Gate Charge Characteristics




Figure 9: Capacitance Characteristics




Figure 10: Power Derating




Figure 11: Current Derating




Figure 12: Safe Operating Area

Typical Characteristics Curves (T_J = 25°C unless otherwise noted)






Figure 13: Normalized Maximum Transient Thermal Impedance

Package Outline Dimensions (Unit: millimeters)


TOLL




Top View



Side View



Bottom View




Front View

NOTES:

1. DIMENSION AND TOLERANCE PER ASME Y14.5M, 1994.
2. ALL DIMENSIONS IN MILLIMETER.
3. DIMENSIONS "E" AND "D1" DO NOT INCLUDE BURRS OR MOLD FLASH. PROTRUSIONS OR GATE BURRS.

DIM.	MILLIMETER		
	MIN.	NOM.	MAX.
A	2.200	2.300	2.400
b	0.650	0.800	0.900
b1	9.650	9.800	9.950
b2	0.400 REF		
c	0.400	0.500	0.600
D	11.480	11.680	11.950
D1	10.250	--	10.700
D2	2.850	--	3.400
E	9.700	9.900	10.100
E1	8.000	--	9.250
e	1.200 BSC		
H1	6.700	7.000	7.300
k	3.000 REF		
k1	4.550 REF		
L	1.350	--	2.100
L1	0.700 REF		
L2	0.600 REF		
L3	0.950	1.200	1.350

Marking Outline



Part Name: GMN026H15LL

1. Logo Mark: 
2. P/N Mark: 026H15LL
3. Date Code: XXXX

Revision History

Version	Date	Major Changes
Rev.A	2025.05.14	Official Release

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.