

16A, 650V Silicon Carbide Schottky Diode

Features


- High-Frequency Operation
- Zero Reverse Recovery Current
- Temperature-Independent Switching
- Extremely Fast Switching
- Plastic package has underwriters Laboratory Flammability Classification 94V-0
- Halogen-free according to IEC 61249-2-21



TO-247AC

Applications

- Boost Diodes in PFC or DC/DC stages
- LED Lighting Power Supplies
- Power Factor Correction



Mechanical Data

- Case: Epoxy, Molded
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead Temperature for Soldering Purposes: 260°C Max. for 10 sec
- Shipped 30 units per plastic tube

Maximum Ratings & Electrical Characteristics (T_A=25°C unless otherwise noted)

Parameter	Symbol	GS16D065SP	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	650	V
Working peak reverse voltage	V _{RWM}	650	V
Maximum DC blocking voltage	V _{DC}	650	V
Maximum average forward rectified current	T _C =25°C	49	A
	T _C =135°C	25	
	T _C =160°C	16	
Peak forward surge current, t _p =10ms, Half Sine Pulse	I _{FSM}	128	A
Power dissipation	T _C =25°C	125	W
	T _C =110°C	54	
Operating junction temperature range	T _J	-55 to +175	°C
Storage temperature range	T _{STG}	-55 to +175	°C

Electrical Specifications ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Test Conditions	Typ	Max	Unit
Forward drop voltage	V_F	$I_F=16\text{A}$, $T_J=25^{\circ}\text{C}$	1.3	1.5	V
		$I_F=16\text{A}$, $T_J=175^{\circ}\text{C}$	1.5	-	
Reverse leakage current @rated V_R	I_R	$V_R=650\text{V}$, $T_J=25^{\circ}\text{C}$	5	50	μA
		$V_R=650\text{V}$, $T_J=175^{\circ}\text{C}$	10	200	
Total capacitive charge	Q_C	$V_R=400\text{V}$, $T_J=25^{\circ}\text{C}$	52	-	nC
Total capacitance	C	$V_R=400\text{V}$, $T_J=25^{\circ}\text{C}$, $f=1\text{MHz}$	83	-	pF

Thermal-Mechanical Specifications ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Typ	Max	Unit
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.2	-	$^{\circ}\text{C}/\text{W}$

Ratings and Characteristics Curves

($T_A = 25^\circ\text{C}$ unless otherwise noted)




Fig.1 –Forward Characteristics




Fig.2 –Reverse Characteristics




Fig.3 –Current Derating




Fig.4 –Capacitance vs. Reverse Voltage




Fig.5 –Total Capacitance Charge vs. Reverse Voltage





Fig.6 –Typical Capacitance Stored Energy

Package Outline Dimensions (Unit: millimeters)


TO-247AC



COMMON DIMENSIONS

SYMBOL	mm		
	Min	Nom	Max
A	4.80	5.00	5.20
A1	2.23	2.41	2.59
A2	1.85	2.00	2.15
b	1.11	1.21	1.36
b2	1.91	2.01	2.21
c	0.51	0.61	0.75
D	20.80	21.00	21.30
D1	16.25	16.55	16.85
E	15.50	15.80	16.10
E1	13.00	13.26	13.56
E2	4.80	5.00	5.20
E3	2.30	2.50	2.70
e	10.88BSC		
L	19.82	19.92	20.22
L1	3.94	4.12	4.30
ØP	3.66	3.68	3.75
ØP1	7.08	7.19	7.30
S	6.15BSC		

Marking Outline



1. Logo Mark:
2. Data code: XXXX
3. Part Name:GS16D065SP
4. Polarity : 

Disclaimers

These materials are intended as a reference to assist our customers in the selection of the Suzhou Good-Ark product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Suzhou Good-Ark Electronics Co., Ltd. or a third party.

Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.

All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Suzhou Good-Ark Electronics Co., Ltd. without notice due to product improvements or other reasons. It is therefore recommended that customers contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized Suzhou Good-Ark Electronics Co., Ltd. for the latest product information before purchasing a product listed herein. The information described here may contain technical inaccuracies or typographical errors. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors. Please also pay attention to information published by Suzhou Good-Ark Electronics Co., Ltd. by various means, including our website home page.

(<http://www.goodark.com>)

When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, Please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Suzhou Good-Ark Electronics Co., Ltd. assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.

The prior written approval of Suzhou Good-Ark Electronics Co., Ltd. is necessary to reprint or reproduce in whole or in part these materials.

Please contact Suzhou Good-Ark Electronics Co., Ltd. or an authorized distributor for further details on these materials or the products contained herein.